

<p>Not permitted!</p>	<p>– Securing / Suspending of stand components or exhibits – Suspended structures connected rigidly or by force of gravity with the hall floor</p>	<p>Permitted!</p>	<p>– Suspension units for lighting systems, cross-beams and banners</p>
<p>Not permitted!</p>	<p>– Carbine swivels unscrewed / screwed – Rope clamps (eccentric) – Tension locks without safety cotter pin or counter nut</p>	<p>Permitted!</p>	<p>BGV- C1 nur mit BGV C1-Zertifikat oder Sekundärsicherung only with BGV C1 certificate or secondary safety</p> <p>WLL nur mit Tragfähigkeitsangabe only with load-carrying capacity information</p> <p>Nur mit Ausdrehsicherung, z.B. Kontermutter und Sicherungssplint only with unscrewing protection, e.g. counter nut and split pin</p> <p>– e.g. shackles with indication of carrying capacity – e.g. quick-connection element with clamping nut (quick link) with indication of carrying capacity</p>
<p>Not permitted!</p>	<p>langgliedrig long-link Textil textile</p> <p>– Long-linked chains (inner length of the link > 3 times the nominal diameter of the chain material) – Textile ropes / plastic coated steel cables</p>	<p>Permitted!</p>	<p>kurzgliedrig Güteklasse 8 DIN 685 short-link quality class 8 DIN 685</p> <p>Stahl DIN 3051 steel DIN 3051</p> <p>– Short-linked chains quality class 8 / DIN 685 – Round strand cable in accordance with EN 12385</p>